

# Truck Mounted Concrete Line Pump PTO Driven Concrete Line Pump Concrete Pump Machinery AI-50CLPP

#### **Basic Information**

Place of Origin: CHINA
Brand Name: JIUHE
Certification: ISO CE
Model Number: 100m3/h

Minimum Order Quantity: 1

Packaging Patallar

40 CON

Packaging Details: 40 CONTAINERDelivery Time: 15 WORKING DAYS

Payment Terms: L/C, T/TSupply Ability: 100SET



## **Product Specification**

Brand: JIUHE
Warranty: 1 Year
Condition: New
Brand Of Diesel Engine: DEUTZ

Keyword: Concrete Line Pump

Main Pump: RexrothCylinder Diameter: 200mmHopper Capacity: 0.6m3

• Max. Aggregate Diameter: Crushed Stone: 40 / Pebble: 50

Max. Delivery Distance: 1000m
Max. Delivery Height: 260m
Max. Horizontal Delivery Distance: 880m

• Max. Theoretical Conveying 100m3/h

Capacity:

O. Hat Diameters 105---



## More Images





#### **Product Description**

Truck mounted Concrete Line Pump PTO Driven Concrete Line Pump Concrete Pump Machinery AI-50CLPP for Australia

#### Truck mounted concrete pump

Jiuhe cooperates with internationally known industrial design company to have the product combined aesthetic thoughts, making it with a all around creative design, then the new vehicular concrete pump was launched after a full research on its reasonable whole layout. Adopting Europe fashionable design idea makes product appearance beautiful, styled, smooth and human-friendly. All of those Giveing customers a great feast, and at the same time, the convenience of operation and maintenance are also increased a lot. Thoughtful attention to every details guarantee product with best quality to the number 1 in domestic market and the leading role in world.

**Lubricating system:**Lubricating system uses automatic multi-point lubricating technology, one-to-one lubrication, and with better performance and prolonged the lifetime of easy wear parts.

**Electrical parts:** Main electric elements are from Schneider and LG, the reliability of the electric-control system is highly improved.

**Automatic protection technology**: Diesel engine startup protection, electric system failure and short circuit protection, auto protection of diesel engine on too high temperature water and low oil pressure, speed limit protection of diesel engine, and quick-stop button.

Quality guaranteeMore reliable service quality and save your cost accordingly. Qingdao Jiuhe Heavy Industry Machinery Co., Ltd. has a high quality after-sales service tem with knowledge and experience, and well equipped, readying to provide service for your equipment, anytime and anywhere. Multi-level, multimode and high efficiency service training make the service team develop all of their skills and each of them an expert in this field. Providing you with high quality pre-sales, sale and after sales service, one-stop total solution and the efficient save system, guaranteeing your equipment running well without worries and maximum save your costs.

ITEM <b>=</b>		UNIT	SPECIFICATION 明
Model型号			JHZ514THB-100-22
Driving system	Chassis brand底品牌		JIEFANG/ CA1167
	Fuel tpye燃料 型		Diesel
	Displacement/Power	L/KW	4.4/162
	Displacement standard排放 准		GB3847/GB17691 National Standard V
	Tyre model 胎型号		9.00R20
	Axle base 距	m	4.9
	quantity of axles 数		2
	Max. driving speed最大行 速 度	Km/h	89
	Front wheel base前 距	mm	1800
	Back wheel base后距	mm	1740
Pumpi ng system	Brand of diesel engine柴油机 品牌		DEUTZ
	Diesel engine model 柴油机型 号		BF6M1013-25T3R
	Diesel engine power柴油机功 率	KW	186
	Driving mode 行		Hydraulic driving
	Main oil pump主油		Rexroth
	Oil cylinder inner diameter × stroke 油缸内径x行程	mm	Φ180×1900
	Concrete cylinder inner diameter × stroke 混凝土缸X行程	mm	Φ230×1900
	Oil pressure of system 系油	МРа	32
	Switch of H-pressure and L- pressure 高低 装置		Equipped
	燃料油缸谷量	L	300
	Oil tank capacity 液油缸容量	L	740
	Cooling mode of hydraulic system 液系冷却形式		Fan cooling 冷
	Hopper capacity料斗容	m <sup>3</sup>	0.6
	Feeding height上料高度	mm	≤1500
	Concrete slump混凝土 落度	ст	14 23
	Max. aggregate diameter 最大骨料粒径	mm	Crushed stone: 40 / Pebble: 50 碎石40卵石50
	Valve管		S Valve S

	Water pump for cleaning 清洗水		water pump
	Concrete pipe cleaning mode 混凝土管路清洗方式		Water cleaning 水洗
	Water tank capacity 水箱容	L	400
	Operation mode 操作方式		Manual /Wire手 ,有 遥控
	Lubrication mode 滑方式		Automatic自
Overall	Length (mm) 度	mm	9195
dimens	Width (mm) 度	mm	2458
		mm	2623
Full-load total weight 重		Kg	13500







## COMPANY









# CERTIFICATE





































# **Customer Visit**



# **Exhibition**



# **Packing**



# **Development strategy**

Strives for the survival by the quality, seek development by science and technology

## Corporate philosophy

People-oriented, science and technology enterprise, recruiting high level scientific and technological personnel, actively introduce advanced technology at home and abroad

#### JiuHe Service

As a professional company, we promise as following:

### JIUHE HEAVEY INDUSTRY MACHINERY service system MAX customer experiences.

#### A. Pre-sales service:

- 1. Selecting the most suitable equipment,
- 2. Designing your personal machinery according to special construction demands,
- 3. Training your technicians to operate our equipment,
- 4. Providing advice to ensure equipment running well in various construction. environments,
- 5. Making new construction scheme if necessary.

#### B. Sales service:

- 1. Equipment delivery transport agent,
- 2. Equipment quality control before delivery,
- 3. Introduce our service system to customers.

#### C. After-sales service:

- 1. Making the first construction scheme,
- 2. Installing and debugging your equipment,
- 3. Troubleshooting on site, prompt and initiative,
- 4. door to door accessories and parts,
- 5. Opportunities to get technical communications with our engineers.

#### D. Value-added service:

- 1. Overall process and zero distance technology tracking service for key projects,
- 2. Carry out large maintenance business,
- 3. Regular equipment checking service,
- 4. Technology update,
- 4. Provide professional periodic maintenance standards for customers.

#### JIUHE HEAVEY INDUSTRY MACHINERY Service Commitments for sold equipment:

- 1. Dispatch technicians to install and debug equipment in time if necessary,
- 2. Provide free maintenance service for the products which have product quality problems within a year after the delivery,
- 3. Provide free operation and maintenance training service for users
- 4. Provide lifelong paid maintenance service, accessories and parts supply for the sold products.



